



# OCEANO 2.1

OCEANO 2.1 AL-BR SQUARE 10° 3000K  
-0,4M

Cod: **CEA03DCS002A00**



**IdroSkud® protection system**  
- polarity reversal protection  
- voltage spikes protection  
- water infiltration protection



**Protection class III**  
Designed to be supplied from a separated extra-low voltage (SELV) power supply



**IP 66**  
Protected against powerful power jets, 100 liters per minute



**IP 68**  
Protected against continuous immersion up to 3 meters



**IK 07**  
Protected against impact of 2 J



**High temperatures**  
Design to withstand temperatures up to +50° C



**Walk-over**  
Fixture design to withstand a static load up to 5 kN



**CX - Extreme**  
corrosion resistance level ISO 9223



**Mizar warranty**  
5 years warranty



## Technical description

Inground luminaire, walk-over, suitable for outdoor environments (IP66/IP68), with operating temperature range: -20°C / +50°C. To provide maximum versatility of application, the body can be made of aluminum or steel; the frame, aluminum, steel or brass. The light source consists of a single 2W power Led chip powered at 24V constant voltage with integrated driver. The luminous flux makes it ideal for tracing pedestrian paths or achieving a starry ceiling effect, thanks to the different emission angles. The source is set back for greater visual comfort. Color rendering index CRI > 90. Oceano is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. There are optionals for anti-glare (honeycomb) and installation accessories (draining and waterproof outercase and spring for ceiling attachment).

### Lighting data

|                             |                       |                      |                                                                                  |
|-----------------------------|-----------------------|----------------------|----------------------------------------------------------------------------------|
| Source type                 | single chip power LED | Photobiological risk | RG0                                                                              |
| CCT                         | 3000K                 | ULR                  | 100.00%                                                                          |
| CRI                         | > 90                  | BUG Rating           | B0 U1 G0                                                                         |
| MacAdam (SDCM)              | 2                     | CIE Flux Code        | 0 0 0 0 100                                                                      |
| Source lumen output (lm)    | 157                   | LED lifetime         | L80 B10 50.000h                                                                  |
| Luminaire lumen output (lm) | 91                    | Efficiency class     | This product contains a light source of energy efficiency class (EU2019/2015): F |
| Light emission              | Narrow                |                      |                                                                                  |
| Beam angle                  | 10°                   |                      |                                                                                  |

### Mechanical data

|                          |                                        |                             |                        |
|--------------------------|----------------------------------------|-----------------------------|------------------------|
| Width (mm)               | 40                                     | Diffuser thickness (mm)     | 6                      |
| Length (mm)              | 40                                     | Class ISO 9223              | CX                     |
| Height (mm)              | 76                                     | Optic type                  | Technopolymer TIR Lens |
| Weight (g)               | 133                                    | Optical optional            | None                   |
| IP Rating                | IP66 / IP68                            | Maximal working temperature | +50° C                 |
| IK rating                | IK07                                   | Minimal working temperature | -20° C                 |
| Shape                    | Square                                 | Maximal static load (kN)    | 5                      |
| Finishing colour         | Aluminium / Brass                      | Walk-over                   | Yes                    |
| Frame material           | Brass                                  | Driver-over                 | No                     |
| Body material            | Anodized 20u aluminum anticorodal 6082 | Maximal surface temperature | +50° C                 |
| External screws material | Stainless steel 316L (A4)              | Areas EN 60598-2-13         | A1 / A2                |
| Diffuser material        | Extraclear tempered glass              |                             |                        |

### Electrical data

|                                 |                                  |                             |                     |
|---------------------------------|----------------------------------|-----------------------------|---------------------|
| Nominal power (W)               | 2                                | Electrical connection       | Parallel connection |
| Power supply (input power type) | Costant voltage - 24V            | Idroskud® protection        | Yes                 |
| Ballast                         | Remote                           | Inverse polarity protection | Yes                 |
| Insulation class                | III                              | Voltage spikes protection   | Yes                 |
| Dimmable                        | Yes                              |                             |                     |
| Power cable type                | H05RN - F 2x0,75 mm <sup>2</sup> |                             |                     |
| Power cable length              | 0,4 m                            |                             |                     |

Photometry

10°



Technical drawing



Accessories



**DRAINING OUTERCASE**

Outercase draining OCEANO 2

Cod: CEAZZ003



**SLIM DRAINING OUTERCASE**

Outercase draining slim OCEANO 2

Cod: CEAZZ004



**SLIM WATER-PROOF OUTERCASE**

Outercase waterproof slim OCEANO 2

Cod: CEAZZ005



**SPRING FOR CEILING MOUNTING**

Spring for ceiling mounting OCEANO 2

Cod: CEAZZ015



**NOT DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 14,4W IP67

Cod: MID0019



**NOT DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 36W IP67

Cod: MID0020



**DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 24W IP67 DALI

Cod: MID0021