



# OCEANO 2.1

OCEANO 2.1 AL-AL SQUARE 10° 3000K  
HONEYCOMB-5M

Cod: **CEA03DCS100H00**



#### IdroSkud® protection system

- polarity reversal protection
- voltage spikes protection
- water infiltration protection



#### Protection class III

Designed to be supplied from a separated extra-low voltage (SELV) power supply



#### IP 66

Protected against powerful power jets, 100 liters per minute



#### IP 68

Protected against continuous immersion up to 3 meters



#### IK 07

Protected against impact of 2 J



#### High temperatures

Design to withstand temperatures up to +50° C



#### Walk-over

Fixture design to withstand a static load up to 5 kN



#### C5 - Very high

corrosion resistance level ISO 9223



#### Mizar warranty

5 years warranty



## Technical description

Inground luminaire, walk-over, suitable for outdoor environments (IP66/IP68), with operating temperature range: -20°C / +50°C. To provide maximum versatility of application, the body can be made of aluminum or steel; the frame, aluminum, steel or brass. The light source consists of a single 2W power Led chip powered at 24V constant voltage with integrated driver. The luminous flux makes it ideal for tracing pedestrian paths or achieving a starry ceiling effect, thanks to the different emission angles. The source is set back for greater visual comfort. Color rendering index CRI > 90. Oceano is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. There are optionals for anti-glare (honeycomb) and installation accessories (draining and waterproof outercase and spring for ceiling attachment).

### Lighting data

|                             |                       |                      |                                                                                  |
|-----------------------------|-----------------------|----------------------|----------------------------------------------------------------------------------|
| Source type                 | single chip power LED | Photobiological risk | RG0                                                                              |
| CCT                         | 3000K                 | ULR                  | 100.00%                                                                          |
| CRI                         | > 90                  | BUG Rating           | B0 U1 G0                                                                         |
| MacAdam (SDCM)              | 2                     | CIE Flux Code        | 0 0 0 0 100                                                                      |
| Source lumen output (lm)    | 157                   | LED lifetime         | L80 B10 50.000h                                                                  |
| Luminaire lumen output (lm) | 91                    | Efficiency class     | This product contains a light source of energy efficiency class (EU2019/2015): F |
| Light emission              | Narrow                |                      |                                                                                  |
| Beam angle                  | 10°                   |                      |                                                                                  |

### Mechanical data

|                  |                                                                                   |                             |                        |
|------------------|-----------------------------------------------------------------------------------|-----------------------------|------------------------|
| Width (mm)       | 40                                                                                | Diffuser thickness (mm)     | 6                      |
| Length (mm)      | 40                                                                                | Class ISO 9223              | C5                     |
| Height (mm)      | 76                                                                                | Optic type                  | Technopolymer TIR Lens |
| Weight (g)       | 102                                                                               | Optical optional            | Honeycomb              |
| IP Rating        | IP66 / IP68                                                                       | Maximal working temperature | +50° C                 |
| IK rating        | IK07                                                                              | Minimal working temperature | -20° C                 |
| Shape            | Square                                                                            | Maximal static load (kN)    | 5                      |
| Finishing colour | Aluminium / Aluminium                                                             | Walk-over                   | Yes                    |
| Frame material   | Anodized 20u aluminum anticorodal 6082, Anodized 20u aluminum anticorodal 6082    | Driver-over                 | No                     |
| Body material    | Alluminio anodizzato 20u anticorodal 6082, Anodized 20u aluminum anticorodal 6082 | Maximal surface temperature | +50° C                 |
|                  |                                                                                   | Areas EN 60598-2-13         | A1 / A2                |

### Electrical data

|                                 |                                  |                             |                     |
|---------------------------------|----------------------------------|-----------------------------|---------------------|
| External screw material         | Stainless steel 316L (A4)        | Electrical connection       | Parallel connection |
| Diffuser material               | Extraclear tempered glass        | Idroskud® protection        | Yes                 |
| Nominal power (W)               | 2                                | Inverse polarity protection | Yes                 |
| Power supply (input power type) | Costant voltage - 24V            | Voltage spikes protection   | Yes                 |
| Ballast                         | Remote                           |                             |                     |
| Insulation class                | III                              |                             |                     |
| Dimmable                        | Yes                              |                             |                     |
| Power cable type                | H05RN - F 2x0,75 mm <sup>2</sup> |                             |                     |
| Power cable length              | 5 m                              |                             |                     |

Photometry

10°



Technical drawing



Accessories



**DRAINING OUTERCASE**

Outercase draining OCEANO 2

Cod: CEAZZ003



**SLIM DRAINING OUTERCASE**

Outercase draining slim OCEANO 2

Cod: CEAZZ004



**SLIM WATER-PROOF OUTERCASE**

Outercase waterproof slim OCEANO 2

Cod: CEAZZ005



**SPRING FOR CEILING MOUNTING**

Spring for ceiling mounting OCEANO 2

Cod: CEAZZ015



**NOT DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 14,4W IP67

Cod: MID0019



**NOT DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 36W IP67

Cod: MID0020



**DIMMABLE POWER SUPPLY**

Power supply 220/240 50/60Hz ON/OFF  
24V 24W IP67 DALI

Cod: MID0021